

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

1-15. (Canceled)

16. (Previously presented) A tyre for vehicle wheels, comprising:

a torus-shaped carcass having a central crown portion and two axially opposite sidewalls terminating in a pair of beads for fixing the tyre onto a corresponding mounting rim, each bead comprising at least one circumferentially unextendable annular reinforcing core comprising a series of spirals of metal wire radially superimposed and axially arranged alongside each other;

a tread strip located on the crown portion and coaxially extending around the carcass and provided with a raised pattern for rolling contact with a road; and

a belt structure coaxially arranged between the carcass and the tread strip;

the carcass having a reinforcing structure comprising at least one ply of rubberized fabric reinforced with metal cords lying in radial planes containing an axis of rotation of the tyre, the reinforcing structure having ends secured to the annular reinforcing cores and a neutral profile, lying in a radial cross-sectional plane, axially extending from bead to bead, wherein:

the neutral profile intersects a cross section of a zone enclosing the annular reinforcing cores; and

the neutral profile has a continuous curvature devoid of inflection points along an extension between the beads.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

17. (Previously presented) The tyre of claim 16, wherein each annular reinforcing core comprises a first axially innermost bead core and a second axially outermost bead core, one end of the at least one ply being inserted between the first and second bead cores.

18. (Previously presented) The tyre of claim 16, wherein the at least one ply comprises a plurality of rubberized-fabric bands alternately arranged, in at least one of the beads, on axially opposite sides of a respective annular reinforcing core.

19. (Previously presented) The tyre of claim 18, wherein the at least one ply comprises two series of bands radially superimposed at least on the crown portion of the tyre.

20. (Previously presented) The tyre of claim 16, wherein the annular reinforcing cores, in a cross-sectional plane, are formed with an irregular trapezoidal shape comprising two bases, a radially internal base and a radially external base, and two inclined sides, an axially internal side and an axially external side.

21. (Previously presented) The tyre of claim 20, wherein a first angle of inclination, with respect to the axis of rotation of the tyre, of the axially internal side of the trapezoidal shape is smaller than a second angle of inclination of the neutral profile

of the reinforcing structure in a region of the axially internal side, and wherein a third angle of inclination, with respect to the axis of rotation of the tyre, of the axially external side of the trapezoidal shape is greater than the second angle of inclination of the neutral profile of the reinforcing structure in the region of the axially external side.

22. (Previously presented) The tyre of claim 20, wherein a longitudinal dimension of the inclined sides of the annular reinforcing cores is between 10 mm and 25 mm, and a transverse dimension of the bases of the annular reinforcing cores is between 7 mm and 20 mm.

23. (Previously presented) The tyre of claim 16, wherein the spirals of metal wire comprise steel with a high carbon content.

24. (Previously presented) The tyre of claim 16, wherein a cross section of the metal wire is hexagonal.

25. (Previously presented) The tyre of claim 16, wherein the annular reinforcing cores comprise a series of radially superimposed spirals of flat metal strip.

26. (Canceled)

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

27. (Currently amended) A method for increasing a load capacity of a tyre for vehicle wheels,

the tyre comprising a torus-shaped carcass having a central crown portion and two axially opposite sidewalls terminating in a pair of beads for fixing the tyre onto a corresponding mounting rim, each bead comprising at least one circumferentially unextendable annular reinforcing core comprising a series of spirals of metal wire radially superimposed and axially arranged alongside each other, the carcass having a reinforcing structure comprising at least one ply of rubberized fabric reinforced with metal cords lying in radial planes containing an axis of rotation of the tyre, the reinforcing structure having ends secured to the annular reinforcing cores and a neutral profile, lying in a radial cross-sectional plane, axially extending from bead to bead, the method comprising the steps of:

limiting the radial extension inwards of the ends of said reinforcing structure so that they do not extend beyond the radially innermost profile of said annular reinforcing cores;

causing the neutral profile to intersect a cross section of a zone enclosing the annular reinforcing cores; and

causing the neutral profile to have a continuous curvature devoid of inflection points along an extension between the beads.

28. (Previously presented) A method for avoiding the application of a twisting torque, in a plane of radial cross section, to annular reinforcing cores in a tyre for vehicle wheels, the annular reinforcing cores comprising a series of spirals of metal wire radially superimposed and axially arranged alongside each other, the tyre comprising a torus-shaped carcass having a reinforcing structure comprising at least one ply of rubberized fabric reinforced with metal cords lying in radial planes containing an axis of rotation of the tyre, the reinforcing structure having ends secured to the annular reinforcing cores and a neutral profile, lying in a radial cross-sectional plane, axially extending from bead to bead, the method comprising the steps of:

avoiding the presence of inflection points along an extension of the neutral profile of the reinforcing structure; and

causing the neutral profile to intersect a cross section of a zone enclosing the annular reinforcing cores.

29. (New) The tyre of claim 16, wherein the annular reinforcing cores, in a cross-sectional plane, are formed with an irregular trapezoidal shape comprising a radially internal base that is inclined with respect to the axis of rotation of the tyre at an angle substantially equal to, or smaller than, that of a bead base on the rim.

30. (New) The tyre of claim 16, wherein the ends of said reinforcing structure extend radially inwards not beyond a radially innermost profile of said annular reinforcing cores.

31. (New) The tyre of claim 16, wherein it is a giant size tyre.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER ^{LLP}

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com